

FUJIAN EPOS ELECTRIC MACHINERY CO., LTD

EMEAN
POWER



FAWDE

ENGINE MODEL: 4DW92-42D

EMEAN POWER

www.emeanpower.com
Email: sale5@fjepos.com
Phone: +86 19890349907

WHATSAPP



WECHAT





Basic technical data

Engine Model	4DW92-42D	
No. of cylinders	4	
Cylinder arrangement	In-line	
Cycle	4 stroke	
Aspiration	Turbocharged	
Cooling system	Water-cooled	
Bore	mm	90 mm
Stroke	mm	100 mm
Compression ratio	17:1	
Displacement	L	2.54 L
Dry engine weight	kg	250 kg
Dimension (L*W*H)	mm	700*590*680
The Flywheel shell interface	SAE4-7.5"	

Performance Data

Governed Engine Speed	r/min	1800
Continuous Power without Fans	kW	31
Standby Power	kW	34
Adaptive power station (kw)	kW	25
Steady state speed regulation rate	%	5 / Mechanical 0-3 / Electronical
Emission Standards	CN Stage II	
Noise Level	dB	≤108
Average effective pressure	mPa	0.81

Lubrication system

Lubricating oil capacity	L	8
Lubricating oil consumption	L/h	≤0.04

Fuel system

Fuel consumption PRP	kg/h	7.07
Fuel consumption Rate	g/kW·h	
25% prime power	g/kW·h	270
50% prime power	g/kW·h	242
75% prime power	g/kW·h	228
100% prime power	g/kW·h	228

100% standby power	g/kW·h	230
--------------------	--------	-----

Air intake system

Air consumption	m ³ /min	2.6
Maximum allowed intake pressure	kPa	6.3
Exhaust gas discharge	m ³ /min	6.4
Exhaust temperature (exhaust gas after turbine)	°C	450
Exhaust heat	kw	23.8
Maximum allowed back pressure	kPa	6.7

Heat balance

Engine heat output	kw	2.5
Heat removal of coolant	kw	20.5
Heat dissipation of intercooler	kw	0

Cooling system

Fan Speed Ratio		1.77
Pump Flow head	L/s	1.4
Coolant capacity-engine	L	6
Fan diameter	mm	400
Fan speed	R/min	3186
Fan flow	m ³ /s/Pa)	1.22/570
Fan power consumption	kW	2.1
Coolant capacity-Radiator	L	8
Thermostat on / off temperature	°C	
Noted:Pump Flow / Speed head		70/2600-6.2

Electrical system

Auxiliary voltage (V)		12 V
Alternator (A)		50
Starter Motor (kw)		3.5
Start preheater (kw)		0.8
Number of teeth of flywheel ring gear		109

Power Calibration Regulations

1.The diesel engine performance data specified above are based on the atmospheric environment specified in the GB/T6072.1/ISO3046-1 standard.

The atmospheric pressure is 100kPa, the ambient temperature is 25°C, and the air humidity is 30%. Fuel calorific value 42.7mJ/kg

2.Prime power refers to the output power that the diesel engine can run for a long time without time limit

under this working condition

3. Standby power refers to that the diesel engine is allowed to work continuously for 1 hour under the limited power of fuel volume every 6 hours

Power correction

1. The diesel engine can be used without reducing the power when the altitude is 400m and the ambient temperature is less than 40°C.

2. When the environment deviates from the standard, the operating power of the diesel engine shall be corrected according to the following table

Altitude < 3000m	%/m	4/500
Altitude > 3000m	%/m	6/500
Ambient Temperature	%/°C	2/5
Humidity	%	No correction

Fuel consumption rate

Unless otherwise specified, the allowable deviation of calibrated fuel consumption rate at rated power is + 5%

EMEAN POWER

www.emeanpower.com

Email: sale5@fjepos.com

Phone: +86 19890349907

WHATSAPP



WECHAT

